

Chapter 24. Zoning
Article V. Districts
Division 2. General Agricultural District, A-1

Sec. 24-218. Height limits.

Structures may be erected up to two stories and shall not exceed 35 feet in height from grade, except that:

- (1) The height limit for buildings may be increased to 45 feet and to three stories; provided, that the two side yards for the building are increased to a minimum of 15 feet plus one foot for each additional foot of the building's height over 35 feet.
- (2) Church spires, belfries, cupolas, monuments, water towers, athletic field lighting, chimneys, flues, flagpoles, home television antennas, home radio aerials, silos and other structures normally associated with and accessory to farming operations and accessory or non accessory wireless communications facilities that utilize alternative mounting structures or are building mounted in accordance with division 6, Wireless Communications Facilities, may be erected to a total height of 60 feet from grade. Camouflaged wireless communications facilities may be erected to a total height of 120 feet from grade.

Upon application for a height limitation waiver, the payment of appropriate fees, notification of adjacent property owners and following a public hearing, the board of supervisors may grant a height limitation waiver for these structures to exceed 60 feet in height but not to exceed 100 feet, from grade to the top of the structure, and for wireless communications facilities that utilize alternative mounting structures or are building mounted to exceed 60 feet in height but not to exceed ~~120 feet in grade to the top of the structure~~ *the maximum approved height of the structure to which it is mounted*, upon finding that:

- a. Such structure will not obstruct light to adjacent property;
 - b. Such structure will not impair the enjoyment of historic attractions and areas of significant historic interest and surrounding developments;
 - c. Such structure will not impair property values in the surrounding area;
 - d. Such structure is adequately designed and served from the standpoint of safety, and the county fire chief finds that the fire safety equipment to be installed is adequately designed and that the building is reasonably well located in relation to fire stations and equipment, so as to offer adequate protection to life and property; and
 - e. Such structure will not be contrary to the public health, safety and general welfare.
- (3) No accessory building which is within 15 feet of any lot line shall be more than one story high. All accessory buildings shall not be more than 45 feet in height; except that silos, barns and other structures normally associated with and accessory to farming operations are controlled by subsection (2) above and may exceed 45 feet in height.
 - (4) Communication towers permitted by a special use permit by the board of supervisors may be in excess of 35 feet in height.

Division 3. Limited Residential District, R-1

Sec. 24-240. Height limits.

Buildings may be erected up to two stories and shall not exceed 35 feet in height from grade, except that:

- (1) The height limit for dwellings may be increased to 45 feet and to three stories; provided, that there are two side yards for each permitted use each of which is a minimum of 15 feet plus one foot or more of side yard for each additional foot of building height over 35 feet.
- (2) A public or semipublic building such as a school, church or library may be erected to a height of 60 feet from grade, provided that the required front, side and rear yards shall be increased one foot for each foot in height over 35 feet.
- (3) Church spires, belfries, cupolas, monuments, water towers, athletic field lighting, chimneys, flues, flagpoles, home television antennae and home radio aerials and wireless communications facilities that utilize alternative mounting structures or are building mounted in accordance with division 6, Wireless Communications Facilities, may be erected to a total height of 60 feet from grade. Camouflaged wireless communications facilities may be erected to a total height of 120 feet from grade. Upon application for a height limitation waiver, the payment of appropriate fees, notification of adjacent property owners and following a public hearing, the board of supervisors may grant a height limitation waiver for these structures to exceed 60 feet in height but not to exceed 100 feet, from grade to the top of the structure, and for wireless communications facilities that utilize alternative mounting structures or are building mounted to exceed 60 feet in height but not to exceed ~~120 feet in grade to the top of the structure~~ *the maximum approved height of the structure to which it is mounted*, upon finding that:
 - a. Such structure will not obstruct light to adjacent property;
 - b. Such structure will not impair the enjoyment of historic attractions and areas of significant historic interest and surrounding developments;
 - c. Such structure will not impair property values in the surrounding area;
 - d. Such structure is adequately designed and served from the standpoint of safety, and the county fire chief finds that the fire safety equipment to be installed is adequately designed and that the building is reasonably well located in relation to fire stations and equipment, so as to offer adequate protection to life and property; and
 - e. Such structure will not be contrary to the public health, safety and general welfare.
- (4) No accessory building which is within 15 feet of any lot line shall be more than one story high. All accessory buildings shall be less than the main building in height; provided, however, the height of an accessory building may exceed the height of the main building if the grade of the lot is such that the elevation of the main building exceeds the elevation of the accessory building. The elevation of the main building and the accessory building shall be measured from the level of the curb or the established curb grade opposite the middle of the main building. In no case shall an accessory building be more than 35 feet in height.

Division 4. General Residential District, R-2

Sec. 24-261. Height limits.

Buildings may be erected up to two stories and shall not exceed 35 feet in height from grade, except that:

- (1) The height limit for dwellings may be increased to 45 feet and to three stories; provided, that there are two side yards for each permitted use each of which is a minimum of 15 feet plus one foot or more of side yard for each additional foot of building height over 35 feet.
- (2) A public or semipublic building such as a school, church or library may be erected to a height of 60 feet from grade, provided that the required front, side and rear yards shall be increased one foot for each foot in height over 35 feet.
- (3) Church spires, belfries, cupolas, monuments, water towers, athletic field lighting, chimneys, flues, flagpoles, home television antennas and home radio aerials and wireless communications facilities that utilize alternative mounting structures or are building mounted in accordance with division 6, Wireless Communications Facilities, may be erected to a total height of 60 feet from grade. Camouflaged wireless communications facilities may be erected to a total height of 120 feet from grade. Upon application for a height limitation waiver, the payment of appropriate fees, notification of adjacent property owners and following a public hearing, the board of supervisors may grant a height limitation waiver for these structures to exceed 60 feet in height but not to exceed 100 feet, from grade to the top of the structure, and for wireless communications facilities that utilize alternative mounting structures or are building mounted to exceed 60 feet in height but not to exceed ~~120 feet in grade to the top of the structure~~ *the maximum approved height of the structure to which it is mounted*, upon finding that:
 - a. Such structure will not obstruct light to adjacent property;
 - b. Such structure will not impair the enjoyment of historic attractions and areas of significant historic interest and surrounding developments;
 - c. Such structure will not impair property values in the surrounding area;
 - d. Such structure is adequately designed and served from the standpoint of safety, and the county fire chief finds that the fire safety equipment to be installed is adequately designed and that the building is reasonably well located in relation to fire stations and equipment, so as to offer adequate protection to life and property; and
 - e. Such structure will not be contrary to the public health, safety and general welfare.
- (4) No accessory building which is within ten feet of any lot line shall be more than one story high. All accessory buildings shall be less than the main building in height; provided, however, the height of an accessory building may exceed the height of the main building if the grade of the lot is such that the elevation of the main building exceeds the elevation of the accessory building. The elevation of the main building and the accessory building shall be measured from the level of the curb or the established curb grade opposite the middle of the main building. In no case shall an accessory building be more than 35 feet in height.

Division 5. Residential Planned Community District, R-4

Sec. 24-293. Height limits.

Structures may be erected up to 60 feet in height from grade to the top of the structure, including all penthouse, electrical, plumbing, elevator, water tank, athletic field lighting, or other accessory functions, which are part of the structure. Camouflaged wireless communications facilities may be erected to a total height of 120 feet from grade. A structure in excess of 60 feet in height but not in excess of 100 feet, from grade to the top of the structure, including all penthouse, electrical, plumbing, elevator, water tank, radio, television and microwave antennas and towers or other accessory functions, and accessory and non accessory wireless communications facilities that utilize alternative mounting structures or are building mounted in accordance with division 6, Wireless Communications Facilities in excess of 60 feet in height but not in excess of ~~120 feet in grade to the top of the structure~~ *the maximum approved height of the structure to which it is mounted*, may be erected only upon the granting of a height limitation waiver by the board of supervisors. Upon application for a height limitation waiver, the payment of appropriate fees, notification of adjacent property owners and following a public hearing, the board of supervisors may grant a height limitation waiver upon finding that:

- a. Such structure is in accordance with the uses, densities, design and traffic analysis shown on the original master plan;
- b. Such structure will not obstruct light from adjacent property;
- c. Such structure will not impair the enjoyment of historic attractions and areas of significant historic interest and surrounding developments;
- d. Such structure will not impair property values in the surrounding area;
- e. Such structure is adequately designed and served from the standpoint of safety and the county fire chief finds that the fire safety equipment to be installed is adequately designed and that the building is reasonably well located in relation to fire stations and equipment, so as to offer adequate protection to life and property; and
- f. Such structure will not be contrary to the public health, safety and general welfare.

Division 6. Multifamily Residential District, R-5

Sec. 24-314. Requirements for improvements and design.

(a) *Sewer and water.* All dwelling units within the Multifamily Residential District, R-5, shall be served by publicly owned and operated sewer and water systems.

(b) *Open space.* At least 35 percent of the gross area of the site shall be retained in open space as defined in section 24-2.

(c) *Recreation.* A playground area or areas with playground equipment shall be provided by the developer. Such areas shall be centrally located and total at least one-half acre for every 50 dwelling units; provided, that the total shall not exceed ten percent of the gross area of the site. For multifamily projects with less than 50 dwelling units, the recreation areas shall total ten percent of the gross acreage of the site. The developer shall provide and install playground equipment specified on the site plan prior to the issuance of any Certificates of Occupancy. Recreation areas and facilities may be deeded to a residents' association.

(d) *Utility lines.* All utility lines, including electrical, telephone and cable television, shall be placed

below ground.

(e) *Parking*. Off-street parking facilities shall be provided in accordance with section 24-53 of this chapter.

(f) *Streets*. All streets shall meet the design and construction requirements of the Virginia Department of Transportation or the requirements of the county subdivision regulations, whichever is greater. All streets shall be consistent with the major thoroughfare plan of the county Comprehensive Plan. The traffic generated by a Multifamily Residential District, R-5, shall not exceed the capacity of adjoining thoroughfares. The daily traffic shall be determined by multiplying the number of proposed dwelling units by the appropriate trip generation rate as listed in the latest edition of a book entitled *Trip Generation* published by the Institute of Transportation Engineers and compared to the existing traffic and road capacity as determined by the highway engineer. The construction of private streets shall be guaranteed by appropriate surety, letter of credit, cash escrow or other form of guarantee approved by the county attorney and director of code compliance.

(g) *Fire hydrants*. Fire hydrants shall be at locations and of types approved by the director of code compliance and county fire chief. No structure within the project shall be further than 400 feet from a hydrant.

(h) *Trash collection*. If containers are provided, they shall be conveniently located to serve all dwelling units. The sites for such containers shall be attractively screened by natural vegetation, landscaping or fences.

(i) *Streetlights*. Streetlights shall be provided, as required by section 24-53(c)(3) of this chapter and the county subdivision ordinance. All streetlights shall be specified on the site plan, generally at intersections and in parking lots and other public areas. The light shall be directed so as not to produce objectionable glare on adjacent property or into residences within the development. No lighting fixture on pedestrian or bicycle paths or parking lots shall exceed a height of 15 feet.

(j) *Structure height*. Structures may be erected up to 35 feet in height from grade to the top of the structure, including all church spires, belfries, cupolas, monuments, penthouse, electrical, plumbing, elevator, athletic field lighting, water tank or other accessory functions which are part of the structure and accessory and non accessory wireless communications facilities that utilize alternative mounting structures, or are building mounted in accordance with division 6, Wireless Communications Facilities. Camouflaged wireless communications facilities may be erected to a total height of 120 feet from grade. A structure in excess of 35 feet in height from grade to the top of the structure, including all church spires, belfries, cupolas, monuments, penthouse, electrical, plumbing, elevator, athletic field lighting, water tank, radio, television and microwave antennas and towers or other accessory functions, *and for wireless communications facilities that utilize alternative mounting structures or are building mounted to exceed 35 feet in height but not to exceed the maximum approved height of the structure to which it is mounted*, may be erected only upon the granting of a height limitation waiver by the board of supervisors. Upon application for a height limitation waiver, the payment of appropriate fees, notification of adjacent property owners and following a public hearing, the board of supervisors may grant a height limitation waiver upon finding that:

- (1) Such structure will not obstruct light from adjacent property;
- (2) Such structure will not impair the enjoyment of historic attractions and areas of significant historic interest and surrounding developments;
- (3) Such structure will not impair property values in the surrounding area;
- (4) Such structure is adequately designed and served from the stand point of safety and the county fire chief certifies that the fire safety equipment to be installed is adequately designed and that the building is reasonably well located in relation to fire stations and equipment, so as to offer adequate protection to life and property; and.

(5) Such structure would not be contrary to the public health, safety and general welfare.

(k) *Maximum number of units and facade variety.* A maximum of ten townhouse units shall be included in one structure. The facade of townhouses within a group shall be changed by variation in the depth of front yards, building materials and/or design so that no more than two abutting units shall be of like appearance.

(l) *Private yards.* Each two-family dwelling unit and each townhouse unit shall open directly into a private yard of a minimum of 200 square feet.

(m) *Minimum distances.* The distance between two main structures on a single lot shall be a minimum of the height of the taller structure. Accessory structures shall be a minimum of ten feet from any other structure.

(n) *Drainage facilities.* Adequate facilities for the control of stormwater, erosion and sedimentation shall be provided in accordance with the *Virginia Erosion and Sediment Control Handbook* and the Virginia Department of Transportation's *Drainage Manual*.

(o) *Natural features and amenities.* Existing features which would enhance the residential environment or the county as a whole such as trees, watercourses, historic spots and similar features shall be preserved to the maximum extent possible.

(p) *Guarantee for improvements.* The zoning administrator shall not issue any certificate of occupancy until the applicant has guaranteed the completion of public improvements, including, but not limited to, public roads, public water and public sewer facilities, shown on the approved site plan by providing either a letter of credit, certified check, cash escrow, cash payment, or other surety, approved by the county attorney.

(q) *Maintenance of common open space, recreation facilities, etc.* The maintenance of common open space, recreation facilities, sidewalks, parking, private streets and other privately owned but common facilities serving the project shall be guaranteed by the developer, project owner or a properly established homeowners' association.

Division 7. Low-Density Residential District, R-6

Sec. 24-335. Height limits.

Buildings may be erected up to two stories and shall not exceed 35 feet in height from grade, except that:

(1) The height limit for dwellings may be increased to 45 feet and to three stories; provided, that the two side yards for the dwelling are increased to a minimum of 15 feet plus one foot for each additional foot of the building's height over 35 feet.

(2) Church spires, belfries, cupolas, monuments, water towers, athletic field lighting, chimneys, flues, flagpoles, home television antennas, home radio aeriols, silos and other structures normally associated with and accessory to farming operations and accessory and non accessory wireless communications facilities that utilize alternative mounting structures or are building mounted in accordance with division 6, Wireless Communications Facilities, may be erected to a total height of 60 feet from grade. Camouflaged wireless communications facilities may be erected to a total height of 120 feet from grade. Upon application for a height limitation waiver, the payment of appropriate fees, notification of adjacent property owners and following a public hearing, the board of supervisors may grant a height limitation waiver for these structures to exceed sixty feet in height but not to exceed 100 feet, from grade to the top of the structure, and for wireless communications facilities that utilize alternative

mounting structures or are building mounted to exceed 60 feet in height but not to exceed 120 feet in grade to the top of the structure ~~the maximum approved height of the structure to which it is mounted,~~ upon finding that:

- a. Such structure will not obstruct light to adjacent property;
- b. Such structure will not impair the enjoyment of historic attractions and areas of significant historic interest and surrounding developments;
- c. Such structure will not impair property values in the surrounding area;
- d. Such structure is adequately designed and served from the standpoint of safety, and the county fire chief finds that the fire safety equipment to be installed is adequately designed and that the building is reasonably well located in relation to fire stations and equipment, so as to offer adequate protection to life and property; and
- e. Such structure will not be contrary to the public health, safety and general welfare.

(3) No accessory building which is within 15 feet of any lot line shall be more than one story high. All accessory buildings shall be less than the main building in height; provided, however, the height of an accessory building may exceed the height of the main building if the grade of the lot is such that the elevation of the main building exceeds the elevation of the accessory building. The elevation of the main building and accessory building shall be measured from the level of the curb or the established curb grade opposite the middle of the main building. In no case shall an accessory building be more than 35 feet in height, except that silos, barns and other structures normally associated with and accessory to farming operations are controlled by subsection (2) above and may exceed the height of the main structure and may exceed 35 feet in height.

Division 8. Rural Residential District, R-8

Sec. 24-354. Height limits.

Structures may be erected up to two stories and shall not exceed 35 feet in height from grade, except that:

(1) The height limit for buildings may be increased to 45 feet and to three stories; provided, that the two side yards for the building are increased to a minimum of 15 feet plus one foot for each additional foot of the building's height over 35 feet.

(2) A public or semipublic building such as a school, church or library may be erected to a height of 60 feet from grade, provided that the required front, rear and side yards shall be increased one foot for each foot in height above 35 feet.

(3) Church spires, belfries, cupolas, monuments, water towers, athletic field lighting, chimneys, flues, flagpoles, home television antennas, home radio aerials, silos and other structures normally associated with and accessory to farming operations and accessory and non accessory wireless communications facilities that utilize alternative mounting structures or are building mounted in accordance with division 6, Wireless Communications Facilities, may be erected to a total height of 60 feet from grade and camouflaged wireless communications facilities may be erected to a total height of 120 feet from grade. Upon application for a height limitation waiver, the payment of appropriate fees, notification of adjacent property owners and following a public hearing, the board of supervisors may grant a height limitation waiver for these structures to exceed 60 feet in height but not to exceed 100 feet, from grade to the top of the structure, and for wireless communications facilities that utilize alternative mounting

structures or are building mounted to exceed 60 feet in height but not to exceed ~~120 feet in grade to the top of the structure~~ *the maximum approved height of the structure to which it is mounted*, upon finding that:

- a. Such structure will not obstruct light to adjacent property;
- b. Such structure will not impair the enjoyment of historic attractions and areas of significant historic interest and surrounding developments;
- c. Such structure will not impair property values in the surrounding area;
- d. Such structure is adequately designed and served from the standpoint of safety, and the county fire chief finds that the fire safety equipment to be installed is adequately designed and that the building is reasonably well located in relation to fire stations and equipment, so as to offer adequate protection to life and property; and
- e. Such structure will not be contrary to the public health, safety and general welfare.

(4) No accessory building which is within 15 feet of any lot line shall be more than one story high. All accessory buildings shall be less than the main building in height; provided, however, the height of an accessory building may exceed the height of the main building if the grade of the lot is such that the elevation of the main building exceeds the elevation of the accessory building. The elevation of the main building and accessory building shall be measured from the level of the curb or the established curb grade opposite the middle of the main building. In no case shall an accessory building be more than 45 feet in height; except that silos, barns and other structures normally associated with and accessory to farming operations are controlled by subsection (3) above and may exceed the height of the main structure and may exceed 45 feet in height.

(5) Communication towers permitted by a special use permit by the board of supervisors may be in excess of 35 feet in height.

Division 9. Limited Business District, LB

Sec. 24-375. Height limits and height limitation waivers.

(a) Structures may be erected up to 35 feet in height from grade to the top of the structure, including all penthouse, electrical, plumbing, elevator, water tank or other accessory functions which are part of or on top of the structure. Parapet walls may be up to four feet above the height of the building on which the walls rest.

(b) Church spires, belfries, cupolas, athletic field lighting, chimneys, flues, monuments, flagpoles and wireless communications facilities that utilize alternative mounting structures or are building mounted in accordance with division 6, Wireless Communications Facilities may be erected to a total height of 60 feet from grade. Camouflaged wireless communications facilities may be erected to a total height of 120 feet from grade. Upon application for a height limitation waiver, the payment of appropriate fees, notification of adjacent property owners and following a public hearing, the board of supervisors may grant a height limitation waiver for these structures to exceed 60 feet in height but not to exceed 100 feet, from grade to the top of the structure, and for wireless communications facilities that utilize alternative mounting structures or are building mounted to exceed 60 feet in height but not to exceed ~~120 feet in grade to the top of the structure~~ *the maximum approved height of the structure to which it is mounted*, upon finding that:

1. Such structure will not obstruct light to adjacent property;
2. Such structure will not impair the enjoyment of historic attractions and areas of significant

historic interest and surrounding developments;

3. Such structure will not impair property values in the surrounding area;

4. Such structure is adequately designed and served from the standpoint of safety, and the county fire chief finds that the fire safety equipment to be installed is adequately designed and that the building is reasonably well located in relation to fire stations and equipment, so as to offer adequate protection to life and property; and

5. Such structure will not be contrary to the public health, safety and general welfare.

(c) All accessory structures shall be less than the main structure in height.

Division 10. General Business District, B-1

Sec. 24-397. Height limits and height limitation waivers.

Structures may be erected up to 60 feet in height from grade to the top of the structure, including all church

spires, belfries, cupolas, athletic field lighting, monuments, flagpoles, penthouse, electrical, plumbing, elevator, water tank or other accessory functions which are part of or on top of the structure and camouflaged wireless communications facilities may be erected to a total height of 120 feet from grade, in accord with the following criteria:

(1) A structure in excess of 60 feet in height but not in excess of 100 feet from grade to the top of the structure, including all church spires, belfries, cupolas, athletic field lighting, monuments, flagpoles, penthouse, electrical, plumbing, elevator, water tank or other accessory functions which are part of or on top of the structure and accessory and non accessory wireless communications facilities that utilize alternative mounting structures or are building mounted in accordance with division 6, Wireless Communications Facilities in excess of 60 feet in height but not in excess of ~~120 feet in grade to the top of the structure~~ *the maximum approved height of the structure to which it is mounted*, may be erected only upon the granting of a height limitation waiver by the board of supervisors. Upon application for a height limitation waiver, the payment of appropriate fees, notification of adjacent property owners and following a public hearing, the board of supervisors may grant a height limitation waiver upon finding that:

a. The regulations of section 24-398 regarding building coverage, floor area ratio and open space are met;

b. Such structure will not obstruct light from adjacent property;

c. Such structure will not impair the enjoyment of historic attractions and areas of significant historic interest and surrounding developments;

d. Such structure will not impair property values in the surrounding area;

e. Such structure is adequately designed and served from the standpoint of safety and the county fire chief finds that the fire safety equipment to be installed is adequately designed and the building is reasonably well located in relation to fire stations and equipment, so as to offer adequate protection to life and property; and

f. Such structure would not be contrary to the public health, safety or general welfare.

(2) Parapet walls may be up to four feet above the height of the building on which the walls rest.

(3) No accessory structure which is within ten feet of any lot line shall be more than one story high. All

accessory structures shall be less than the main structure in height.

Division 14. Planned Unit Development District, PUD

Sec. 24-496. Height and spacing of structures.

(a) Structures may be erected up to 60 feet in height from grade to the top of the structure, including all church spires, belfries, cupolas, athletic field lighting, monuments, flagpoles, penthouse, electrical, plumbing, elevator, water tank or other accessory functions which are part of the structure and accessory and non accessory wireless communications facilities that utilize alternative mounting structures or are building mounted in accordance with division 6, Wireless Communications Facilities. Camouflaged wireless communications facilities may be erected to a total height of 120 feet from grade.

(b) A structure in excess of 60 feet in height but not in excess of 100 feet from grade to the top of the structure, including all church spires, belfries, cupolas, athletic field lighting, monuments, flagpoles, penthouse, electrical, plumbing, elevator, water tank, radio, television, and microwave antennas and towers or other accessory functions, and accessory and non accessory wireless communications facilities that utilize alternative mounting structures or are building mounted in accordance with division 6, Wireless Communications facilities in excess of 60 feet in height but not in excess of ~~120 feet~~ ~~in grade to the top of the structure~~ *the maximum approved height of the structure to which it is mounted*, may be erected only upon the granting of a height limitation waiver by the board of supervisors.

Upon application for a height limitation waiver, the payment of appropriate fees, notification of adjacent property owners and following a public hearing, the board of supervisors may grant a height limitation waiver upon finding that:

- (1) Such structure is in accordance with the uses, densities, design and traffic analysis shown on the original master plan;
- (2) Such structure will not obstruct light from adjacent property;
- (3) Such structure will not impair the enjoyment of historic attractions and areas of significant historic interest and surrounding developments;
- (4) Such structure will not impair property values in the surrounding area;
- (5) Such structure is adequately designed and served from the standpoint of safety, and the county fire chief finds that the fire safety equipment to be installed is adequately designed and that the building is reasonably well located in relation to fire stations and equipment, so as to offer adequate protection to life and property; and
- (6) Such structure would not be contrary to the public health, safety or general welfare.

Division 15. Mixed-Use, MU

Sec. 24-525. Height of structures.

(a) Structures may be erected up to 60 feet in height from grade to the top of the structure, including all church spires, belfries, cupolas, athletic field lighting, monuments, flagpoles, penthouse, electrical, plumbing, elevator, water tank or other accessory functions which are part of the structure and accessory and non accessory wireless communications facilities that utilize alternative mounting structures or are building mounted in accordance with division 6, Wireless Communications Facilities. Camouflaged wireless communications facilities may be erected to a total height of 120 feet from grade.

(b) A structure in excess of 60 feet in height but not in excess of 100 feet from grade to the top of the structure, including all church spires, belfries, cupolas, athletic field lighting, monuments, flagpoles, penthouse, electrical, plumbing, elevator, water tank, radio, television and microwave antennas, and towers or other accessory functions, and accessory and non accessory wireless communications facilities that utilize alternative mounting structures or are building mounted in accordance with division 6, Wireless Communications Facilities in excess of 60 feet in height but not in excess of ~~120 feet in grade to the top of the structure~~ *the maximum approved height of the structure to which it is mounted*, may be erected only upon the granting of a height limitation waiver by the board of supervisors.

(c) Upon application for a height limitation waiver, the payment of appropriate fees, notification of adjacent property owners and following a public hearing, the board of supervisors may grant a height limitation waiver upon finding that:

- (1) Such structure is in accordance with the uses, densities, design and traffic analysis shown on the original master plan;
- (2) Such structure will not obstruct light from adjacent property;
- (3) Such structure will not impair the enjoyment of historic attractions and areas of significant historic interest and surrounding developments;
- (4) Such structure will not impair property values in the surrounding area;
- (5) Such structure is adequately designed and served from the standpoint of safety and the county fire chief finds that the fire safety equipment to be installed is adequately designed and that the structure is reasonably well located in relation to fire stations and equipment, so as to offer adequate protection to life and property; and
- (6) Such structure would not be contrary to the public health, safety or general welfare.

Division 16. Public Land District, PL

Section 24-535.9. Height limits.

Structures may be erected up to two stories and shall not exceed 35 feet in height from grade, except that:

- (1) The height limit for buildings may be increased to 60 feet, provided that the required front, rear and side yards shall be increased one foot for each foot in height above 35 feet.
- (2) Spires, belfries, cupolas, monuments, water towers, athletic field lighting, chimneys, flues,

flagpoles, home television antennas, home radio aerials, silos and other structures normally associated with and accessory to farming operations and accessory and non accessory wireless communications facilities that utilize alternative mounting structures or are building mounted in accordance with division 6, Wireless Communications Facilities, may be erected to a total height of 60 feet from grade and camouflaged wireless communications facilities may be erected to a total height of 120 feet from grade. Upon application for a height limitation waiver, the payment of appropriate fees, notification of adjacent property owners and following a public hearing, the board of supervisors may grant a height limitation waiver for these structures to exceed 60 feet in height but not to exceed 100 feet, from grade to the top of the structure, and for wireless communications facilities that utilize alternative mounting structures or are building mounted to exceed 60 feet in height but not to exceed ~~120 feet in grade to the top of the structure~~ *the maximum approved height of the structure to which it is mounted*, upon finding that:

- a. Such structure will not obstruct light to adjacent property;
- b. Such structure will not impair the enjoyment of historic attractions and areas of significant historic interest and surrounding developments;
- c. Such structure will not impair property values in the surrounding area;
- d. Such structure is adequately designed and served from the standpoint of safety, and the county fire chief finds that the fire safety equipment to be installed is adequately designed and that the building is reasonably well located in relation to fire stations and equipment, so as to offer adequate protection to life and property; and
- e. Such structure will not be contrary to the public health, safety and general welfare.

(3) No accessory building which is within 15 feet of any lot line shall be more than one story high. All accessory buildings shall be less than the main building in height; provided, however, the height of an accessory building may exceed the height of the main building if the grade of the lot is such that the elevation of the main building exceeds the elevation of the accessory building. The elevation of the main building and accessory building shall be measured from the level of the curb or the established curb grade opposite the middle of the main building. In no case shall an accessory building be more than 45 feet in height; except that silos, barns and other structures normally associated with and accessory to farming operations are controlled by subsection (2) above and may exceed the height of the main structure and may exceed 45 feet in height.

(4) Communication towers permitted by a special use permit by the board of supervisors may be in excess of 35 feet in height.